



## **ESD CONTROL SYSTEMS**

**PLOT NO.41, VENKATESHWARA ENCLAVE, SUCHITRA “X” ROADS, JEEDIMETLA,  
HYDERABAD – 500067. T.G. India. Phone Nos. 9848022354, 9989118686, 040-48571678**

**Mail: [esdcontrolsystems@gmail.com](mailto:esdcontrolsystems@gmail.com), [info@esdcs.in](mailto:info@esdcs.in), Website: [www.esdcs.in](http://www.esdcs.in)**

**GST: 36ADFPP2338G1ZL - PAN: ADFPP2338G - HSN: 90318000 – SAC: 998393**

### **Operating and Maintenance of Electro Static Discharge Touch Pad - Model No. TPNH-0919 For Non-Hazardous Areas**

- 1. The Touch Pad is to be installed near the entrance.**
- 2. Connect the Touch Pad with the Earth leads provided as per the Instructions given in the Data Sheet.**
- 3. Touch the Pad with Full Palm with firm contact.**
- 4. Wait till the Red LED turns to Green LED with Audio Alert and then remove your hand. This indicates that your body is grounded and all Static Charges are dissipated and your body is having no Static Charges.**
- 5. Replace the battery if no LED lights and Audio Alert.**
- 6. Keep the Touch Pad a way from direct Sun Light and Moisture.**
- 7. Clean the Touch Pad periodically with wet cloth. Do not use any solvents or detergents.**

**For any clarification, please contact the manufacturer.**